


**Emergency Lighting Fixture : Item Code - PEL 118 E/NE (T)
Mounting : Wall, (Type – Non - Emergency)**



A wall mounting fitting, consist of single FT – L which provides illumination on normal mains power supply and the same lamp/s continues to provide illumination during mains failure on self contained battery source. **ON** resumption of mains supply, the lamp/s switches back to the mains automatically & simultaneously starts recharging the battery to the required level. **Non- Emergency models provide uninterrupted illumination.**

Dimensions (in mm)



TECHNICAL SPECIFICATIONS

MONOGRAM OF PROLITE

Confirms	IS : 9583 – 1981.
Ingress Protection	IP – 20.
Housing	Made up of C. R. C. A. Sheet steel – 22 S. W. G.
Paint & Colour	Epoxy polyester powder coating, White in colour.
Diffuser cum Message Panel	CAD Designed & cut vinyl on 2 M. M. thick milky acrylic/polycarbonate.
Lamp Holder	FT – L, T 8 : 18 Watts – Base G 13 White polycarbonate/ABS with electrical grade brass contacts.
Input (V)	~ 230 Volts, 50 Hz.
Lamp	1 x FT – L 18 Watts.
Lamp make	Osram, Philips, Surya.
Mains Connector	5 A, 250 Volts, Milky white Polycarbonate with electrical grade brass contacts.
Mounting	Wall fixing with 2 Nos. of holes.
Weight (Kg)	1 kg. Approx
Application	Large area domestic & commercial purpose, corridors of hotels, Battery rooms, staircases, underground parking.

Tolerance on overall dimensions is ± 5 m. m. unless otherwise specified.

Please Note: Other Input Voltage Is Also Available – Price On Request (**POR**).

Due to continuous development, specifications may change without prior notice.

FOR

PROLITE AUTOGLO LIMITED

DATE :