


**Emergency Lighting Fixture : Item Code - PEL 108 E/M/WP (1)
Mounting : Wall/Ceiling, (Type - Maintained)**



Consist of single or more FT - Ls which provides illumination on normal mains power supply and the same lamp/s continues to provide illumination during mains failure on self contained battery source. **ON** resumption of mains supply, the lamp/s switches back to the mains automatically & simultaneously starts recharging the battery to the required level.
Maintained models provide uninterrupted illumination.

Dimensions (in mm)



TECHNICAL SPECIFICATIONS

MONOGRAM OF PROLITE

Confirms	IS : 9583 - 1981.
Ingress Protection	IP - 65.
Housing	Molded ABS, white in colour.
Diffuser cum Message panel	Molded milky ABS, reeded finish.
Reflector	Molded ABS, white in colour.
Lamp Holder	FT - L, T 5 : 8 Watts White Polycarbonate/ABS with electrical grade brass contacts.
Input (V)	~ 230 Volts, 50 Hz.
Lamp	1 x FT - L (T - 5) 8 Watts.
Lamp make	ST OR Equivalent
Mains Connector	5 A, 250 Volts, PCB Mount with electrical grade brass contacts.
Battery type	Ni-Mh/Ni-Cd, rechargeable.
Duration	120 Minutes back up; \pm 10%.
Charging Type	Constant current charger.
Recharging Cycle	16 to 24 hours recharging period.
Mounting	Surface mounting type.
Application	For outdoors of domestic & commercial premises, corridors of hotels, Battery & pump rooms, staircases, underground parking.

Tolerance on overall dimensions is \pm 5 m. m. unless otherwise specified.

Please Note: Other Input Voltage Is Also Available - Price On Request (**POR**).

Due to continuous development, specifications may change without prior notice.

FOR,

PROLITE AUTOGLO LIMITED