


**Emergency Lighting Fixture : Item Code - PEL 111 E/NE
Mounting : Wall, (Type – Non Emergency)**



A wall mounting fitting, consist of single CF – L which provides illumination on normal mains power supply only.

Dimensions (in mm):



TECHNICAL SPECIFICATIONS

MONOGRAM OF PROLITE

| | |
|----------------------------|---|
| Confirms | IS : 9583 – 1981. |
| Ingress Protection | IP – 20. |
| Housing | Made up of C. R. C. A. Sheet steel – 22 S. W. G. |
| Paint & Colour | Epoxy polyester powder coating, White in colour. |
| Diffuser cum message panel | CAD Designed & cut vinyl on 2 M. M. thick milky acrylic. |
| Lamp Holder | 2 pins, straight, Base : GX23 White polycarbonate/ABS with electrical grade brass contacts. |
| Input (V) | ~ 230 Volts, 50 Hz. |
| Lamp | 1 x CF – L 11 Watts. |
| Lamp make | Osram, Philips, Surya |
| Mains Connector | 5 A, 250 Volts, Milky white Polycarbonate with electrical grade brass contacts. |
| Weight (Kg) | 1 Kg. Approx |
| Application | Domestic & commercial purpose, corridors of hotels, Battery rooms, staircases, underground parking. |

Tolerance on overall dimensions is ± 5 m. m. unless otherwise specified.

Please Note: Other Input Voltage Is Also Available – Price On Request (**POR**).

Due to continuous development, specifications may change without prior notice.

FOR,

PROLITE AUTOGLO LIMITED