

**Emergency Lighting Fixture : Item Code - PEL 120 E/NE
Mounting : Wall, (Type – Non Emergency)**



A wall mounting fitting, consist of single FT – L which provides illumination on normal mains power supply only.

Dimensions (in mm)



TECHNICAL SPECIFICATIONS

MONOGRAM OF PROLITE

Confirms	IS : 9583 – 1981.
Ingress Protection	IP – 20.
Housing	Made up of C. R. C. A. Sheet steel – 22 S. W. G.
Paint & Colour	Epoxy polyester powder coating, White in colour.
Diffuser cum Message panel	2 M. M. Milky acrylic diffuser with CAD Designed & cut vinyl pasted.
Lamp Holder	Base : G13, Rotor holder suitable for (T – 12) FT – L, White polycarbonate/ABS with electrical grade brass contacts.
Input (V)	~ 230 Volts, 50 Hz.
Lamp	1 x FT – L 18/20 Watts.
Lamp make	Osram< Philips, Surya
Mains Connector	5 A, 250 Volts, Milky white Polycarbonate with electrical grade brass contacts.
Mounting	Ceiling/wall mounting with 2 Nos. of holes
Weight (Kg)	4 Kg. Approx
Application	Domestic & commercial purpose, corridors of hotels, Battery rooms, staircases, underground parking.
Tolerance on overall dimensions is \pm 5 m. m. unless otherwise specified.	
Please Note: Other Input Voltage Is Also Available – Price On Request (POR).	
Due to continuous development, specifications may change without prior notice.	

FOR

PROLITE AUTOGLO LIMITED

DATE :